

Hose & **C**ouplings **F**or **A**frica cc



INDUSTRIAL

RUBBER

HOSE



Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Activia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Green-Stripe Mining Hose

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	NO. OF PLIES	APPROX. MASS (kg/m)
NOM.	ACT.				
10	9,5	17,5	1200	2	0,20
12.5	12,7	21,7	1200	2	0,34
16	15,9	25,3	1200	2	0,42
20	19,1	28,1	1100	2	0,47
25	25,4	35,2	1000	2	0,65
32	31,8	43,8	500	2	1,21
40	38,1	49,5	500	2	1,48
45	44,5	55,7	500	2	2,39
50	50,8	62,7	500	2	1.90
63	63,5	75,8	500	2	3,20
75	76,2	88,1	500	2	3,80
100	101,6	113,1	500	2	4,80

Recommended for:

Underground mining and industrial air and water pressure applications. This range meets the requirements of L.D. SABS 988 Specification up to 25mm, 32mm to 100mm has 3 : 1 safety factor.

Liner:

Type F, NR/SBR compound.

Reinforcement:

Two plies of high strength synthetic yarn spirally applied.

Cover:

Weather and abrasion resistant NR/SBR compound with a green colored identification stripe.

Recommended Temp. Range:

-20 °C to + 80 °C

Hose Ends:

Plain

Lengths:

Up to 25mm ID – 30, 60
32 to 100 mm ID – 30m.

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Activia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Gold Stripe Mining Hose

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	NO. OF PLIES	APPROX. MASS (kg/m)
NOM.	ACT.				
10	9,5	20,1	1700	2	0,34
12.5	12,7	23,1	1700	2	0,41
16	15,9	26,7	1550	2	0,51
20	19,1	29,5	1350	2	0,60
25	25,4	36,8	1000	2	0,78
32	31,8	49,5	1000	2	1,31
40	38,1	54,3	1000	2	1,61
45	44,5	60,7	1000	2	2,52
50	50,8	66,7	1000	2	2,00
63	63,5	79,8	1000	2	3,39
75	76,2	92,1	1000	2	4,00
100	101,6	117,1	1000	2	5,15

Recommended for:

Air and water pressure applications where maximum resistance to arduous service conditions is required. This range meets the requirements of H.D. SABS 988 Specification up to 50mm, and is widely accepted as an outstanding heavy duty mining and industrial hose.

Liner:

Type F, NR/SBR compound.

Reinforcement:

Two plies of high tensile synthetic yarn spirally applied.

Cover:

Weather and abrasion resistant NR/SBR compound with a yellow colored identification stripe.

Recommended Temp. Range:

-20°C to + 80 °C

Hose Ends:

Plain

Lengths:

Up to 25mm ID – 30, 60

32 to 100 mm ID – 30m.

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Oil Resistant Mining Hose

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	NO. OF PLIES	APPROX. MASS (kg/m)
NOM.	ACT.				
10	9,5	17,5	1700	2	0,35
12.5	12,7	21,7	1700	2	0,41
16	15,9	25,3	1550	2	0,52
20	19,1	28,1	1350	2	0,61
25	25,4	35,2	1000	2	0,80
32	31,8	51,1	850	2	1,63
40	38,1	56,8	750	2	1,91
50	50,8	65,5	750	2	2,40
63	63,5	86,3	750	2	3,87
75	76,2	98,6	750	2	4,52
100	101,6	123,6	750	2	5,15

Recommended for:

Air and water pressure applications where resistance to heat, oil and oily vapours are required. Especially suitable for heavy duty air line, oil lubricated, pneumatic tools.

Liner:

Oil resistant synthetic compound.

Reinforcement:

Two plies of high tensile synthetic yarn spirally applied.

Cover:

Type F, weather and abrasion resistant NR/SBR compound with a red colored identification stripe.

Recommended Temp. Range:

-20 °C to + 80 °C

Hose Ends:

Plain

Lengths:

Up to 25mm ID – 30m lengths

32 to 100 mm ID – 30m lengths

Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8

Fax: 011 822 7538

Cell: 083 271 1590

078 108 8554

e-mail: sales@hoseandcouplings.co.za



Fire Reel Hose

SIZE ID (mm)	SIZE OD (mm)	WP (kpa)
20	27.5	1000

Recommended for:

Fire reel applications which will not flatten or distort while coiled in a reel, in use the hose will remain flexible and resist kinking.

Liner:

Black synthetic rubber

Reinforcement:

High strength synthetic yarn.

Cover:

Smooth red synthetic rubber, EPPM cover

Recommended Temp. Range:

-25 °C to + 120 °C

Available Lengths:

Standard 30m lengths.

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Water Suction Hose Light Duty

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	SUCTION (kpa)	MIN. BEND RADIUS (mm)
NOM.	ACT.				
32	31,8	47	500	70	4 x OD
38	39.0	52.4	500	70	4 x OD
50	50.4	65.1	500	70	4 x OD
63	63.5	78.6	500	70	4 x OD
75	75.8	92.1	500	70	4 x OD
100	100.8	117.1	500	70	4 x OD

Recommended for:

General suction and delivery applications

Liner:

NR Compound

Reinforcement:

Galvanized wire helix embedded between two plies of braided synthetic yarn.

Cover:

NR compound ,weather and abrasion resistant.

Recommended Temp. Range:

-20 °C to + 80 °C

Lengths:

Standard 30m lengths.

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Water Suction Hose Heavy Duty

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	SUCTION (kpa)	MIN. BEND RADIUS (mm)
NOM.	ACT.				
32	32.3	47.0	1000	80	4 x OD
38	38.0	52.7	1000	80	4 x OD
45	44.4	59.1	1000	80	4 x OD
50	50.4	65.1	1000	80	4 x OD
63	63.5	78.6	1000	80	4 x OD
75	75.8	96.1	1000	80	4 x OD
100	100.8	121.1	1000	80	4 x OD

Recommended for:

General suction and delivery applications

Liner:

NR Compound

Reinforcement:

Galvanized wire helix embedded between two plies of braided synthetic yarn.

Cover:

NR compound, weather and abrasion resistant.

Recommended Temp. Range:

-20 °C to + 80 °C

Lengths:

Standard 30m lengths.

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Activia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Furnace Coolant Hose Non Conductive Type

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	APPROX. MASS (kg/m)
NOM.	ACT.			
20	19,1	34,6	1000	1,00
25	25,4	40,4	1000	1,20
32	31,8	50,5	1000	1,78
38	38,1	58,6	1000	1,74
42	41,4	63,3	1000	2,21
45	44,5	65,0	1000	2,31
48	47,6	69,4	1000	2,47
50	50,8	71,6	1000	2,56
57	57,2	79,0	1000	2,87
63	63,5	83,1	1000	3,14
75	76,2	94,4	1000	4,10
100	101	123	1000	4.89

NB: RED AND WHITE LINER AVAILABLE

Recommended for:

Conveyance of coolant water in foundries where the hose is required to have electrically non-conductive

Properties and be resistant to a high temperature environment.

Liner:

Type E, non conductive EPDM compound. (Red liner)

Reinforcement:

Multiple plies of synthetic fabric.

Cover:

One ply of rubber impregnated heat shield fabric.

Recommended Temp. Range:

Hose is protected against high temperature external, environmental conditions.

Hose Ends:

Plain

Lengths:

15 and 30m lengths only

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Blue Welding Hose

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	APPROX. MASS (kg/m)	SPEC. NO.	LENGTHS (m)
NOM.	ACT.					
6.3	6.3	14.7	1200	0.19	1062	RANDOM
8	7.9	16.0	1200	0.22	1062	RANDOM
8	7.9	16.0	1200	0.22	1062	18
8	7.9	16.0	1200	0.22	1062	30
8	7.9	16.0	1200	0.22	1062	50
8	7.9	16.0	1200	0.22	1062	100
10	9.5	18.0	1200	0.25	1062	30
12.5	12.7	20.3	1200	0.26	1062	30

Recommended for:

All welding and cutting applications requiring light, flexible hose conforming to SABS Specification 582.

Liner:

Type F, Ignition resistant NR/SBR compound.

Reinforcement:

Two spiral plies of synthetic yarn .

Cover:

Colored for gas identification – red or blue. Weather and abrasion resistant NR/SBR compound.

* Red - for acetylene

* Blue - for oxygen

Hose Ends:

Plain

Lengths:

Set lengths, as well as long random lengths available. Hoses cannot be joined into longer lengths.

6m,12m,18m,30m,50m,100m-random lengths included-8mm welding hose only.

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Red Welding Hose

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	APPROX. MASS (kg/m)	LENGTHS (m)
NOM.	ACT.				
6,3	6,3	14,7	1200	0,19	RANDOM
8	7,9	16,0	1200	0,22	RANDOM
8	7.9	16,0	1200	0,22	18
8	7.9	16,0	1200	0,22	30
8	7.9	16,0	1200	0,22	50
8	7.9	16,0	1200	0,22	100
10	9,5	18,0	1200	0,25	30
12,5	12,7	20,3	1200	0,26	30

Recommended for:

All welding and cutting applications requiring light, flexible hose conforming to SABS Specification 582.

Liner:

Type F, Ignition resistant NR/SBR compound.

Reinforcement:

Two spiral plies of synthetic yarn .

Cover:

Colored for gas identification – red or blue. Weather and abrasion resistant NR/SBR compound.

* Red - for acetylene

* Blue - for oxygen

Hose Ends:

Plain

Lengths:

Set lengths, as well as long random lengths available. Hoses cannot be joined into longer lengths.

6m,12m,18m,30m,50m,100m-random lengths included-8mm welding hose only.

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Smooth Cover Black Air Line Hose

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	NO. OF PLIES	APPROX. MASS (kg/m)
NOM.	ACT.				
6.0	6.3	14	1500	2	0.19
8.0	7.9	16	1500	2	0.22
10.0	9.5	17	1500	2	0.26

Recommended for:

Industrial air and water pressure applications,

Liner:

NR/SBR compound.

Reinforcement:

Two plies of high tensile synthetic yarn spirally applied.

Cover:

Smooth weather and abrasion resistant SBR compound. (Black).

Recommended Temp. Range:

-20°C to + 80 °C

Hose Ends:

Plain

Lengths:

Long random lengths with a minimum of 30m and 100m coils available.

Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Orange Domestic Gas Hose

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	NO. OF PLIES	APPROX. MASS (kg/m)
NOM.	ACT.				
6.0	6.3	14	1500	2	0.19
8.0	7.9	16	1500	2	0.22
10.0	9.5	17	1500	2	0.26

Recommended for:

Recommended for hose connection between LP gas storage cylinders and domestic appliances,
Also suitable for use as **oil resistant airline hose** – SABS 1156

Liner:

Type B, LP gas resistant nitrile compound.

Reinforcement:

Two spiral plies of synthetic yarn.

Cover:

Type B, Orange cover PVC/NBR oil, heat and weather resistant compound.

Recommended Temp. Range:

-20 °C to + 90 °C

Hose Ends:

Plain

Lengths:

Sizes under 10mm available in long random lengths, 60m lengths include

Sizes above 10mm available in 30m and 60m lengths

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Air Brake Hoses
(SAE J1402-unarmoured)

HOSE ID (mm)	APPROX. OD (mm)	RATED WP (kpa)	NO. OF PLIES
12.5	22.0	1550	2

Recommended for:

Air activated automotive brake systems.

Liner:

Nitrile compound

Reinforcement:

Plies of braided high strength synthetic yarn.

Cover:

Weather & abrasion resistant, Neoprene Compound.

Recommended Temp. Range:

-20 °C to + 80 °C

Available Lengths

Available in 100m lengths

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Bulk Suction and Delivery Fuel Road Tanker HOSE

HOSE ID (mm)	APPROX. OD (mm)	RATED WP (kpa)	SUCTION (kpa)
32	32.3	1050	80
38	38.0	1050	80
50	50.4	1050	80
63	63.5	1050	80
75	75.8	1050	80
100	100.8	1050	80

Recommended for:

Petrol discharge and conveying fuels with an aromatic content not exceeding 50%

Liner:

Type B Nitrile compound

Reinforcement:

Galvanized wire helix embedded between two plies of braided synthetic yarn.

Cover:

Type B, weather & abrasion resisting nitrile compound.

Recommended Temp. Range:

-20 °C to + 80 °C

Available Lengths:

Standard 30m lengths

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Flexible Braided Kerbside Petrol Pump Hose

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	SUCTION (kpa)	MIN. BEND RADIUS (mm)	APPROX. MASS (kg/m)
NOM.	ACT.					
16	15,9	26,0	1000	70	55	0,46
16 (G)	15,9	26,0	1000	70	55	0,46
20	19,1	31,0	1000	70	60	0,75
25	25,4	37,0	1000	70	75	0,90

Recommended for:

Pump dispensing of petrol and diesel fuels (with an aromatic content not exceeding 60%) and where flexibility and good reeling characteristics are required.

Liner:

Type B, nitrile compound.

Reinforcement:

Single brass wire braid for flexibility.

Cover:

Type A, weather & abrasion resisting neoprene or hypalon compound.

Recommended Temp. Range:

-25 C to + 60 C

Available Lengths:

30 and 60m lengths

Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Farm Fuel Tank Hose Orange

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)	APPROX. MASS (kg/m)
NOM.	ACT.			
25	25,4	34,7	500	0,61

Recommended for:

Gravity or low pressure discharge of petrol and diesel fuels from overhead storage tanks found on farms and construction sites.

Liner:

Type B, nitrile compound.

Reinforcement:

Two spiral plies of synthetic yarn

Cover:

Type B, Orange PVC/NBR compound – oil, weather and abrasion resistant.

Recommended Temp. Range:

-20 C to + 40 C

Available Lengths:

2.5m and 30m lengths

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenvue, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Tanker Discharge Hose

HOSE ID (mm)	APPROX. OD (mm)	RATED WP (kpa)	SUCTION (kpa)
100	115	350	60

Recommended for:

Petrol discharge and conveying fuels with an aromatic content not exceeding 50%

Liner:

Nitrile compound

Reinforcement:

Galvanized wire helix embedded between two plies of braided synthetic yarn.

Cover:

Type B, weather & abrasion resisting nitrile compound.

Recommended Temp. Range:

-20 °C to + 80 °C

Available Lengths

4, 4.5 & 6 meters.

Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenvue, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**


Tel: 011 822 7427/8

Fax: 011 822 7538

Cell: 083 271 1590

078 108 8554

e-mail: sales@hoseandcouplings.co.za



Cementation Hoses

HOSE ID (mm)	APPROX OD (mm)	RATED WP (kpa)
75	95.8	500
100	120.8	500

Recommended for:

Handling cement powder. Hose incorporates an abrasion resistant liner. It can be used to discharge cement in bulk from road tankers.

Liner:

6mm abrasion resistant

Reinforcement:

2 plies textile reinforced (softwall construction)

Cover:

Natural rubber weather resistant and ozone resistant.

Recommended Temp. Range:

-25 °C to + 60 °C

Available Lengths:

Maximum 18m lengths only-also available in 125mm id

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenvue, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Sand /Shot blast Hose Light Duty

HOSE ID (mm)	APPROX. OD (mm)	RATED WP (kpa)
32	48,4	750
40	54,1	750
45	61,1	750
50	68,0	750

Recommended for:

Sand and shot blast applications, where extremely robust, but flexible hose is required.

Liner:

Abrasion resistant, SBR compound.

Reinforcement:

Multiple plies of synthetic textile fabric

Cover:

Weather and abrasion resistant NR/SBR compound.

Recommended Temp. Range:

-20 °C to + 80 °C

Lengths:

Standard 30m lengths.

Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenvue, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8

Fax: 011 822 7538

Cell: 083 271 1590

078 108 8554

e-mail: sales@hoseandcouplings.co.za



Sand /Shot blast Hose Heavy Duty

HOSE ID (mm)	APPROX. OD (mm)	RATED WP (kpa)
20	37,1	1200
25	44,0	1200
32	54,0	1200
40	65,0	1200
50	78,0	1200
63	87,0	1200
75	96,0	1200

Recommended for:

Heavy duty Sand and shot blast applications, where extremely robust, but flexible hose is required.

Liner:

Abrasion resistant, SBR compound.

Reinforcement:

Multiple plies of synthetic textile fabric

Cover:

Type F weather and abrasion resistant NR/SBR compound.

Recommended Temp. Range:

-20 °C to + 80 °C

Lengths:

Standard 30m lengths.

Hose & Couplings For Africa cc


CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Beverage Hose
Beer and Milk

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)
NOM.	ACT.		
25	25.4	42.4	1400
32	31.8	52.1	1400
40	38.1	60.2	1000
50	50.8	73.8	1000
63	63.5	87.0	1000
75	76.2	99.7	1000
100	101.6	125.1	1000

Recommended for:

Conveying Beer, Milk and Fruit Juices

Liner:

White Natural Rubber (Non Tainting)

Reinforcement:

Multiple plies of braided synthetic yarn.

Cover:

Type F, weather & abrasion resistant blue NR/SBR compound.

Recommended Temp. Range:

-20 °C to + 80 °C (also suitable for intermittent sterilization @ 120 °C)

Hose Ends:

Plain

Lengths:

18metres

30m-softwall and hardwall hose available made to FDA standards

Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



Beverage Hose Wine

HOSE ID (mm)		APPROX. OD (mm)	RATED WP (kpa)
NOM.	ACT.		
50	50.4	67.4	700
63	63.5	84.5	700
75	75.8	96.8	700

Recommended for:

Delivery of wine (not suitable for spirits)

Liner:

Type F Red food grade NR com,pound

Reinforcement:

Galvanized wire helix between multiple plies of woven textile fabric.

Cover:

Red weather& abrasion resistant compound.

Recommended Temp. Range:

-20 °C to + 80 °C (also suitable for intermittent sterilization @ 120 °C)

Hose Ends:

Plain

Lengths:

18metres

Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenvue, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8

Fax: 011 822 7538

Cell: 083 271 1590

078 108 8554

e-mail: sales@hoseandcouplings.co.za



SATURATED STEAM HOSE

4

APPLICATION: Multipurpose steam hose used in construction, shipping and petrochemical industries


TEMPERATURE: -30°C + 230°C

TUBE: EPDM, black, smooth

REINFORCEMENT: 2 High tensile steel braids

COVER: SBR/EPDM, red, pin-pricked, smooth cloth impression-heat abrasion and ozone resistant

CODE	ID/INCH	ID/mm	WP/Bar	WP/PSI
HP18-13-25	1/2	13	18	261
HP18-19-32	3/4	19	18	261
HP18-25-38	1	25	18	261



Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8

Fax: 011 822 7538

Cell: 083 271 1590

078 108 8554

e-mail: sales@hoseandcouplings.co.za



MILK AND FATTY FOODS HOSE

7



APPLICATION: Delivery of milk and other dairy products, edible oils and non-alcoholic beverages

TEMPERATURE: -30°C + 100°C

NORM: FDA

TUBE: NBR, white, smooth, food quality-caustic resistance of up to 50%

REINFORCEMENT: High tensile textile cord embedded between layers

COVER: SBR/EPDM, blue, smooth with cloth impression

CODE	ID/INCH	ID/mm	WP/Bar	WP/PSI
FSDNBR-38-48	1 1/2	38	10	145
FSDNBR-51-61	2	51	10	145
FSDNBR-76-88	3	76	10	145



Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenvue, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8

Fax: 011 822 7538

Cell: 083 271 1590

078 108 8554

e-mail: sales@hoseandcouplings.co.za



MULTIPURPOSE HOSE

10

APPLICATION: Non-conductive multipurpose hose

TEMPERATURE: -30°C + 85°C

TUBE: NBR, black, smooth

REINFORCEMENT: High tensile textile cords

COVER: CR, red with cloth impression

CODE	ID/INCH	ID/mm	WP/Bar	WP/PSI
MP20-13-23	1/2	13	20	290
MP20-19-29	3/4	19	20	290
MP20-25-37	1	25	20	290



Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8
Fax: 011 822 7538
Cell: 083 271 1590
078 108 8554

e-mail: sales@hoseandcouplings.co.za



CHEMICAL SUCTION AND DELIVERY HOSE



APPLICATION: Suction and delivery of 98% of known acids and chemicals

TEMPERATURE: -30°C + 80°C

TUBE: UHMWPE, smooth

REINFORCEMENT: High tensile textile cord, steel wire embedded between layers

COVER: EPDM, black with cloth impression, abrasion/oil and weather resistant

CODE	ID/INCH	ID/mm	WP/Bar	WP/PSI
UPE16-25-37	1	25	16	232
UPE16-32-44	1 1/4	32	16	232
UPE16-38-50	1 1/2	38	16	232
UPE16-51-67	2	51	16	232
UPE16-76-92	3	76	16	232
UPE16-102-118	4	102	16	232



Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8

Fax: 011 822 7538

Cell: 083 271 1590

078 108 8554

e-mail: sales@hoseandcouplings.co.za



HYDRAULIC HOSE-4SH

14



APPLICATION: Hydraulic systems with high peak pressures and arduous operating conditions

TEMPERATURE: -40°C + 100°C

NORM: Din 20023 part 2 type 4SH

TUBE: NBR, black, oil resistant

REINFORCEMENT: 4 High tensile steel spirals

COVER: SBR, black, abrasion, oil and weather resistant

CODE	ID/INCH	ID/mm	WP/Bar	WP/PSI
4SH-12	3/4	19	420	6091
4SH-16	1	25	380	5511
4SH-20	1 1/4	32	325	4713
4SH-24	1 1/2	38	290	4205
4SH-32	2	51	250	3625



Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenvue, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8

Fax: 011 822 7538

Cell: 083 271 1590

078 108 8554

e-mail: sales@hoseandcouplings.co.za



HYDRAULIC HOSE-4SP

13

APPLICATION: Hydraulic systems with high peak pressures and arduous operating conditions

TEMPERATURE: -40°C + 100°C

NORM: Din 20023 part 1 type 4SP

TUBE: NBR, black, oil resistant

REINFORCEMENT: 4 High tensile steel spirals

COVER: SBR, black, abrasion, oil and weather resistant

CODE	ID/INCH	ID/mm	WP/Bar	WP/PSI
4SP-06	3/8	10	445	6453
4SP-08	1/2	13	415	6018
4SP-10	5/8	16	350	5076
4SP-12	3/4	19	350	5076
4SP-16	1	25	280	4060
4SP-20	1 1/4	32	210	3045
4SP-24	1 1/2	38	185	2683
4SP-32	2	51	175	2538

[TO PRODUCTS
INDEX](#)



Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenvue, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8

Fax: 011 822 7538

Cell: 083 271 1590

078 108 8554

e-mail: sales@hoseandcouplings.co.za



HYDRAULIC HOSE -1SN

APPLICATION: Hydraulic systems with high peak pressures and arduous operating conditions

TEMPERATURE: -40°C to +100°C

NORM: Din 20022 part 1 type 1SN

TUBE: NBR, black, oil resistant

REINFORCEMENT: 1 High tensile steel spiral

COVER: SBR, black, abrasion, oil and weather resistant

CODE	ID/INCH	ID/MM	WP/BAR	WP/PSI
1SN-04	1/4	6.4	225	3263
1SN-05	5/16	8	215	3118
1SN-06	3/8	10	180	2610
1SN-08	1/2	13	160	2320
1SN-10	5/8	16	130	1885
1SN-12	3/4	19	105	1523
1SN-16	1	25	88	1276
1SN-20	1 1/4	32	63	914
1SN-24	1 1/2	38	50	725
1SN-32	2	51	40	580

Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenview, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8

Fax: 011 822 7538

Cell: 083 271 1590

078 108 8554

e-mail: sales@hoseandcouplings.co.za



HYDRAULIC HOSE -2SN

APPLICATION: Hydraulic systems with high peak pressures and arduous operating conditions

TEMPERATURE: -40°C to +100°C

NORM: Din 20022 part 1 type 2SN

TUBE: NBR, black, oil resistant

REINFORCEMENT: 2 High tensile steel spirals

COVER: SBR, black, abrasion, oil and weather resistant

CODE	ID/INCH	ID/MM	WP/BAR	WP/PSI
2SN-04	1/4	6.4	400	5800
2SN-05	5/16	8	350	5075
2SN-06	3/8	10	330	4785
2SN-08	1/2	13	275	3988
2SN-10	5/8	16	250	3625
2SN-12	3/4	19	215	3118
2SN-16	1	25	165	2393
2SN-20	1 1/4	32	125	1813
2SN-24	1 1/2	38	90	1305
2SN-32	2	51	80	1160

Hose & Couplings For Africa cc

CK 2006/095406/23

182 North Reef Rd,
Adivia Park, Elandsfontein
P.O. Box 752 308,
Gardenvue, 2047

**SPECIALISTS IN INDUSTRIAL
HOSES & COUPLINGS**

Tel: 011 822 7427/8

Fax: 011 822 7538

Cell: 083 271 1590

078 108 8554

e-mail: sales@hoseandcouplings.co.za



HYDRAULIC HOSE -1SN

APPLICATION: Hydraulic systems with high peak pressures and arduous operating conditions

TEMPERATURE: -40°C to +100°C

NORM: Din 20022 part 1 type 1SN

TUBE: NBR, black, oil resistant

REINFORCEMENT: 1 High tensile steel spiral

COVER: SBR, black, abrasion, oil and weather resistant

CODE	ID/INCH	ID/MM	WP/BAR	WP/PSI
1SN-04	1/4	6.4	225	3263
1SN-05	5/16	8	215	3118
1SN-06	3/8	10	180	2610
1SN-08	1/2	13	160	2320
1SN-10	5/8	16	130	1885
1SN-12	3/4	19	105	1523
1SN-16	1	25	88	1276
1SN-20	1 1/4	32	63	914
1SN-24	1 1/2	38	50	725
1SN-32	2	51	40	580